



CYCLO[®] INDUSTRIES, INC. MATERIAL SAFETY DATA SHEET

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Also, make this information available to any employee who requests it.

If Cyclo Industries, Inc. considers the formula of this product to be a trade secret, the exact chemical names of the ingredient(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists and other health professionals.

SECTION 1 – PRODUCT & COMPANY IDENTIFICATION

Product Name: Rally[®] Performance™ Fast Oil™ Treatment, Stock No. 82400

Product Use: Improves acceleration, maximizes horsepower, reduces fuel consuming friction and drag.

Manufactured by: Cyclo Industries, Inc., 401 Maplewood Drive, Suite 18, Jupiter, FL 33458
Telephone: (561) 775-9600

First Aid Emergency: (800) 752-7869 or (312) 906-6194

Shipping Emergency: (800) 424-9300 or (703) 527-3887 (CHEMTREC)

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

| CAS Reg. No. | Material | Percentage | Exposure Limits |
|--------------|----------|------------|-----------------|
|--------------|----------|------------|-----------------|

This product does not contain any hazardous ingredients.

SECTION 3 – HAZARDS IDENTIFICATION

Effects of Overexposure:

Ingestion: Essentially nontoxic product may cause irritations.
Inhalation: Vapors of overheated product may cause irritations.
Skin Contact: On prolonged contact, irritation may occur.
Eye Contact: May cause irritation.

Carcinogenicity: NTP Carcinogen = No; IARC Monographs = No; OSHA Regulated = No

Health Hazards (Acute and Chronic): The polymer and mineral oil are acute, essentially non-toxic. Chronic effects are not known.

Medical Conditions Generally Aggravated By Exposure: None known.

SECTION 4 – FIRST AID MEASURES

First Aid Procedures:

- Skin Contact: Wipe off excess, wash with soap and water.
Inhalation: In case of inhalation of overheated product, move from source of exposure and inhale fresh air.
Consult physician.
Eye Contact: Immediately rinse eyes with eyelids retracted for at least 15 minutes with water. Consult physician.

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point: 335°F (168°C) **Method Used:** COC

Flammable Limits in Air by Volume: Not determined

Extinguishing Media: Foam, dry chemical, water spray or carbon dioxide

Special Fire Fighting Procedures: Wear full protective fire gear including self-contained breathing apparatus with full face piece.

Unusual Fire and Explosion Hazards: Product of combustion includes fumes, smoke and carbon monoxide.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spill/Leak Procedures: Report spills as required to appropriate authorities. On the ground, use sawdust, diatomaceous earth, scrape and remove.

SECTION 7 – HANDLING AND STORAGE

Handling & Storage Procedures: No special measures necessary. See product label for additional information. KEEP OUT OF THE REACH OF CHILDREN.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection: Necessary only when handling overheated product. Use respirator with cartridge to remove organic chemical vapors.

Ventilation:

| | |
|-----------------------|---------------|
| Local Exhaust Rate: | May be used |
| Special: | Not necessary |
| Mechanical (General): | May be used |

Protective Gloves: PVC type

Eye Protection: Chemical worker goggles.

Work/Hygienic Practices: Eye washes and safety showers in the workplace are recommended.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: >395°F (>202°C)

Specific Gravity (H₂O=1): 0.88

Vapor Pressure (mmHg) at about 70°F: <<1

Vapor Density (Air=1): >1 (heavier than air)

Solubility in Water: Not soluble

pH: Not determined

Evaporation Rate (Butyl Acetate = 1): <<1 (slower)

Appearance and Odor: Clear pale yellow with low oily odor

Volatile Organic Compound (VOC) (as packaged minus water): Not determined

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: Overheating of product, long term temperature limit 215° F.

Incompatibility (materials to avoid): Strong oxidizing agents.

Hazardous Decomposition or Byproducts: On overheating, irritating oil vapors are formed.

Hazardous Polymerization: Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

Toxicological Data: Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

SECTION 12 – ECOLOGICAL INFORMATION

Aquatic/Terrestrial Toxicity Environmental Fate No data is available at this time.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. Do not flush to drain. Before attempting clean up, refer to other sections of this MSDS for hazard caution information.

SECTION 14 – TRANSPORT INFORMATION

U.S. DOT **Shipping Description:** Not regulated
ID Number: Not regulated
Hazard Class: Not applicable
Packing Group: Not applicable
Label: Not applicable
Placards: Not applicable

IMDG **Shipping Description:** Not regulated
ID Number: Not regulated
Hazard Class: Not applicable
Packing Group: Not applicable
Label: Not applicable
Markings: Not applicable
Placards: Not applicable

SECTION 15 – REGULATORY INFORMATION

TSCA Inventory: All components of this product are listed on the Toxic Substance Control Act (TSCA) Inventory of chemical substances maintained by the U.S. Environmental Protection Agency.

SARA Extremely Hazardous Substances None

SARA Section 313 This product does not contain any toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (SARA 313 – Toxic Chemical Release Reporting)

CERCLA/Superfund (RQ): This product is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

California Proposition 65: This product does not contain chemicals known to the State of California to cause cancer, birth defects and other reproductive harm.

SECTION 16 – OTHER INFORMATION

Document Date: 12/01/2007 **Supersedes:** 5/07/2004

Revisions: Cyclo Industries incorporated

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or

reliance upon this information.