



CYCLO[®] INDUSTRIES, LLC

MATERIAL SAFETY DATA SHEET

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Also, make this information available to any employee who requests it.

If Cyclo Industries, LLC considers the formula of this product to be a trade secret, the exact chemical names of the ingredient(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists and other health professionals.

SECTION 1 – PRODUCT & COMPANY IDENTIFICATION

Product Name: Rally Performance™ Trans Boost™, Stock No. 82470

Product Use: Improves acceleration. Stops transmission leaks. Maximizes power and transmission performance. Cleans gum and varnish from transmission parts restoring smooth operations. Cures common causes of transmission malfunction.

Manufactured by: Cyclo Industries, LLC
401 Maplewood Drive, Suite 18, Jupiter, FL 33458
Telephone: (561) 775-9600

First Aid Emergency: (800) 752-7869 or (312) 906-6194

Shipping Emergency: (800) 424-9300 or (703) 527-3887 (CHEMTREC)

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

CAS Reg. No.	Material	Percentage	Exposure Limits
61788-76-91	Proprietary	10 – 20	Not established
67-63-0	Isopropanol	0.01 - 5	400 ppm = OSHA TWA
1330-20-7	Xylene with ethyl benzenes	0.01 - 6	100 ppm = OSHA TWA
108-88-3	Toluene	0.01 - 5	50 ppm = OSHA TWA
123-42-2	Diacetone alcohol	0.01 – 2	50 ppm = OSHA TWA

SECTION 3 – HAZARDS IDENTIFICATION

Effects of Overexposure:

Not available

Carcinogenicity: NTP Carcinogen = No; IARC Monographs = No; OSHA Regulated = No

SECTION 4 – FIRST AID MEASURES**First Aid Procedures:**

- Ingestion: DO NOT induce vomiting. Give milk or water. Keep warm and quiet and get immediate medical attention. Never give anything by mouth to an unconscious person.
- Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Follow up with soap and water wash as soon as possible. Wash clothing before use. If irritation persists, seek medical attention.
- Inhalation: Remove from exposure. If not breathing, give artificial respiration. Keep at rest. Get immediate medical attention.
- Eye Contact: Flush eyes immediately with plenty of water for at least 15 minutes. Obtain immediate medical attention.

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point: 43°F (6°C) **Method Used:** Cleveland Open Cup

Flammable Limits in Air by Volume: Lower Limit = 0.7% Upper Limit = 7.0%

Extinguishing Media: Foam, water spray (fog), dry chemical, carbon dioxide

Special Fire Fighting Procedures: Use water spray, dry chemical, foam or carbon dioxide. Use water to keep fire exposed, containers cool

Unusual Fire or Explosion Hazard: Treat as a petroleum oil fire.

HMIS Code: Health = 2 Flammability = 2 Reactivity = 0

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spill/Leak Procedures: Eliminate sources of ignition and ventilate area. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Take up small spills with dry chemical absorbent. Do not take up with any flammable material, such as sawdust. Large spills may be taken up with pump or vacuum and finished off with dry chemical absorbent. Liquid too viscous for pumping may be scraped up. Consult an expert on disposal of recovered material.

SECTION 7 – HANDLING AND STORAGE

Handling & Storage Procedures: Do not get in eyes, on skin or clothing. Do not take internally. Wash thoroughly after handling. Avoid breathing mist or vapor. Use only with adequate ventilation. Keep away from heat, sparks, open flame and fire. Keep containers closed when not in use. Store in cool, dry, well-ventilated area away from sources of ignition. See product label for additional information. **KEEP OUT OF THE REACH OF CHILDREN.**

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection: Full facepiece, NIOSH approved organic vapor respirator.

Ventilation: LOCAL – Use to capture vapor/mist if necessary
MECHANICAL – Use in confined areas

Protective Gloves: Resistant to chemical penetration

Eye Protection: Safety glasses with splash guards or full face shield is recommended.

Work/Hygienic Practices: Eye washes and safety showers in the workplace are recommended.

Other: Use explosion proof machinery.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: IBP approx. 555°F (290°C) **Specific Gravity (H₂O=1):** 0.87 – 0.88

Vapor Pressure: < 0.1 mm @ 20°C **Vapor Density (Air=1):** Greater than 5

Solubility in Water: Negligible <0.1% @ 1 Atmosphere and 25°C

Evaporation Rate (Butyl Acetate = 1): Less than 0.01

Appearance and Odor: Light yellow liquid – nil to bland odor.

Volatile Organic Compound (VOC) (as packaged minus water):

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable **Conditions to Avoid:** Heat, sparks, open flame

Incompatibility (materials to avoid): Strong oxidizing agents – liquid chlorine, concentrated oxygen, sodium and calcium hypochlorites.

Hazardous Decomposition or Byproducts: Combustion may yield fumes, smoke, oxides of sulfur and nitrogen, carbon monoxide and HCl.

Hazardous Polymerization: Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

Toxicological Data: Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

SECTION 12 – ECOLOGICAL INFORMATION

Aquatic/Terrestrial Toxicity Environmental Fate No data is available at this time.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. Before attempting clean up, refer to other sections of this MSDS for hazard caution information.

SECTION 14 – TRANSPORT INFORMATION**U.S. DOT**

Shipping Description: Consumer Commodity
ID Number: Not regulated
Hazard Class: ORM-D
Packing Group: Not applicable
Label: Not applicable
Placards: Not applicable

IMDG

Shipping Description: Flammable Liquids, N.O.S., Ltd. Qty. (Contains Isopropanol, Xylene and Toluene)
ID Number: UN1993
Hazard Class: 3
Packing Group: II
Label: Not applicable
Markings: Not applicable
Placards: Not applicable

SECTION 15 – REGULATORY INFORMATION

TSCA Inventory: All components of this product are listed on the Toxic Substance Control Act (TSCA) Inventory of chemical substances maintained by the U.S. Environmental Protection Agency.

SARA Extremely Hazardous Substances None

SARA Section 313 This product contains the following toxic chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (SARA 313 – Toxic Chemical Release Reporting)

<u>Chemical Name</u>	<u>CAS#</u>	<u>Weight %</u>
Isopropanol	1330-20-7	0.01 - 4
Xylene with ethyl benzenes	67-63-0	0.01 - 6
Toluene	108-88-3	0.01 - 2

SECTION 15 – REGULATORY INFORMATION continued**CERCLA/Superfund (RQ):**

<u>Chemical Name</u>	<u>Reportable Quantity</u>
Xylene	100 lbs.
Toluene	1000 lbs.

California Proposition 65: Toluene**SECTION 16 – OTHER INFORMATION****Document Date:** March 16, 2005**Supersedes:** June 18, 2004**Revisions:** Section 1 – new address; Section 2 – corrected CAS# for Xylene.

Cyclo Industries, LLC provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, LLC makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, LLC will not be responsible for damages resulting from use of or reliance upon this information.