

TECHNICAL DATA



Rally® Performance™

Fast OIL™

**Improves Acceleration
& Maximizes Horsepower**

Stock No. 82400

REDUCES FRICTION & DRAG:

Improves Acceleration - Lubrication experts have found that 75% to 80% of engine wear occurs at start up. Fast OIL provides lubrication protection, reducing wear at this critical time.

Reduces Fuel Consuming Friction - proprietary additive chemistry bonds to internal engine surfaces, reducing the coefficient of friction and provides added lubrication protection, reducing wear at this critical time.

Maximizes Horsepower - the engine will accelerate better at lower or higher speeds & produce maximum power

Contains Extreme Pressure & Anti-Wear Barrier - additives in even the best motor oils are gradually depleted which, can result in premature engine wear. Rally Performance *Friction Barrier* chemistry provides the best extreme pressure protection.

ADD TO OIL: Cars & Sport Trucks

DIRECTIONS: 1. Add to existing oil. DO NOT OVERFILL. 2. On next oil change, drain oil and change oil filter. 3. Refill oil to recommended level replacing 12 oz. of oil with Fast Oil. 4. Operate vehicle as usual, changing oil & filter as recommended by owner's manual. For top performance, re-treat with Fast Oil every oil change. Fast Oil is so effective at eliminating wear that it should not be used in new engines until the break-in period is completed (usually 2,000 miles).

PHYSICAL PROPERTIES

Size	12 fl. oz. / 354 mL	Cases per pallet	190
Package	plastic bottle	Cases per layer	38
Flash Point	335°F	Layers per pallet	5
Specific Gravity (H ₂ O = 1)	0.88 @ 60°F	Cube	0.22
Appearance	clear pale yellow liquid	Case Weight	5 lbs
Solubility in Water	Not Soluble	UPC (Bottle)	0 89269 82400 8
Boiling Point	>395°F	UPC (Carton)	1 00 89269 82400 5