

TECHNICAL DATA



Rally® Performance™

Fuel POWER™

Total Fuel System Cleaner

Stock No. 82420

Deposit build-up causes poor acceleration, hesitation, rough running, knock, stalling, engine run-on and poor gas mileage. Fuel Power is a blend of concentrated synthetic cleaners formulated to help restore original power, acceleration & octane requirements in 3 steps.

1. Cleans Fuel Injectors & Carburetors

Deposit Problems: deposits clog injectors, foul spray patterns, rob power, cause hesitation, increase emissions **Fuel Power Solution:** Dissolves olefin deposits in injector nozzles to improve starting and save gas, reduce emissions and increase power.

2. Cleans Intake Valves, Manifolds


Deposit Problems: valve deposits disrupt the proper flow of fuel and air into the combustion chamber. This can rob power, increase emissions & cause poor *driveability*. **Fuel Power Solution:** Cleans intake valves, manifolds & ports to reduce emissions, engine run-on and restore lost power.

3. Reduces Combustion Chamber & Intake Port Deposit

Deposit Problems: deposits in the combustion chamber takes up space which increases compression ratios and disrupts smooth fuel flow. This can cause knocking, pinging, poor acceleration, increased emissions. **Fuel Power Solution:** Provides a noticeable performance difference - reduces hesitation, reduces knock, ping, & run-on, and improves acceleration. It's like using a higher-octane gasoline.

- Restores maximum power plus reduces emissions
- Cleans injectors, carburetors, intake valves, and combustion chambers clean
- Controls octane requirement increase
- Reduces nitrous oxide emissions (NO_x) hydrocarbon (HC), carbon monoxide (CO)
- Improves fuel economy
- Improves acceleration
- Improves starting
- Eliminates knock & hesitation
- Safe for catalytic converters
- Provides fuel stability during storage

DIRTY **CLEAN**



Directions: 1. When gas tank is nearly empty, pour entire contents of container into tank. 2. Refuel with up to 18 gallons of fuel. A second treatment may be helpful to very dirty engines.

Preventive Maintenance: Fuel Power works best to maintain like new engine performance if new car owners use it before 10,000 miles and on a regular basis. This is "preventive maintenance" to keep the deposits from first forming.

PHYSICAL PROPERTIES

Size	16 fl. oz. / 473 mL	Cases per pallet	170
Package	plastic bottle	Cases per layer	34
Flash Point	145-185°F	Layers per pallet	5
Boiling Range	480-640°F (249-338°C)	Cube	0.25
Specific Gravity (H ₂ O = 1)	0.8728	Case Weight	6.2 lbs
Appearance	Colorless to pale yellow liquid	UPC (Bottle)	0 89269 82420 6
Solubility in Water	Negligible	UPC (Carton)	1 00 89269 82420 3