

Super Heavy Duty DOT 4 BRAKE FLUID

Stock Nos. C-71, C-72, C-73

HIGH TEMP FORMULA 450°F MIN. BOILING POINT For Disc & Drum Brakes

Cyclo Super Heavy Duty DOT 4 Brake Fluid exceeds requirements of SAE Spec-J1703, Federal Spec VV-B-680a, and Federal Motor Vehicle Safety Standard 116 for DOT 3 brake fluid for dependable performance in both disc and drum brakes.

- Resists oxidation and corrosion
- Protects rubber seals
- Compatible with ALL vehicles where DOT 4 brake fluid is recommended by car manufacturers.

Registration: Cyclo Brake Fluid is properly registered in all states where special registration is required (Alabama, Colorado, Florida & Texas) and is registered with American Association of Motor Vehicles Administration (AAMVA) in Washington, D.C.

PHYSICAL PROPERTIES

			<u>per Pallet</u>	<u>per Layer</u>	<u>per Pallet</u>
Size:	C-71	12 fl. oz. / 350 mL			
	C-72	32 fl. oz. / 946 mL			
	C-73	1 gal. / 3.78 liter	C-71	18	10
Package:	plastic bottles/drum		C-72	70	7
Wet Boiling Point:	284°F Minimum – Per DOT 4 Specification		C-73	60	5
Dry Boiling Point:	450 – 490°F				
Specific Gravity (H ₂ O=1):	8.6				
Appearance:	Amber color liquid				
Evaporation Rate:	0.01		C-71	0.35	11.5
Solubility in Water:	100%		C-72	0.89	28.2
Storage Caution:	Each container has a foil seal to insure fresh, moisture proof brake fluid. Store brake fluid only in its original container. Keep container clean & tightly closed to prevent absorption of moisture. Keep out of reach of children.		C-73	0.89	36.3