






Select the Cyclo diesel product that's right for you!

Diesel fuel itself is the cause of major operational inefficiencies in diesel engines in both warm and cold weather conditions. The physical and chemical composition of diesel fuel, if untreated, will cause waxing, clogged fuel lines, fouled injectors, and excessive smoking. All this can be treated and avoided with Cyclo products!

<p>Problems:</p> <ul style="list-style-type: none"> • Wax formation • Ice crystals • Poor stability • Blocked fuel filters and lines • Poor combustion • Power loss • Hard starting 	<p>Problems:</p> <ul style="list-style-type: none"> • Loss of efficiency and power • Plugged injectors and injector nozzles • Poor performance • Wasted fuel • Black smoke 	<p>Problems:</p> <ul style="list-style-type: none"> • Blocked fuel filters and fuel lines • Poor performance 	<p>Problems:</p> <ul style="list-style-type: none"> • Black smoke • Lost power • Filter plugging • Corrosion & rust • Wasted fuel 	<p>Problems:</p> <ul style="list-style-type: none"> • Gelled fuel • Frozen filters • Wax formation • Corrosion & rust • Fuel line & filter icing 	<p>Problems:</p> <ul style="list-style-type: none"> • Residues and bacterial growth cause sludge
<p>Solution:</p> <p>Use year around for maximum power</p> <p>Cyclo Anti-Gel Diesel Fuel Treatment used regularly helps</p> <ul style="list-style-type: none"> • Provide up to 50% lower operating temperature than untreated fuel • Attack & overpower paraffin wax • Melt ice crystals on contact • Prevent filter plugging • Disperse water • Coat the system to prevent ice from sticking • Maintain fuel stability • Reduce varnish & carbon buildup • Keep fuel injectors clean 	<p>Solution:</p> <p>Use regularly to keep injectors clean, save fuel and reduce smoke emissions</p> <p>Cyclo Diesel Fuel Injector Cleaner used regularly helps:</p> <ul style="list-style-type: none"> • Clean injectors • Save fuel • Reduce sm oke emissions • Restore power • Provide fuel stability during storage • Replace lubricity for low sulfur fuel 	<p>Solution:</p> <p>Cyclo Diesel Water Remover used regularly helps:</p> <ul style="list-style-type: none"> • Disperse water • Reduce freezing point of water in fuel • Clean injectors • Improve diesel performance 	<p>Solution:</p> <p>Problem solver – Diesel Clean Exhaust™</p> <ul style="list-style-type: none"> • Reduce sm oke up to 50% • Save fuel • Restore power • Provide fuel stability during storage • Reduce filter plugging • Replace lubricity for low sulfur fuel • Reduce corrosion & rust 	<p>Solution:</p> <p>Problem solver – "Fast Action" Diesel Instant Thaw™ quickly dissolves gelled fuel and:</p> <ul style="list-style-type: none"> • Thaws frozen fuel filters • Disperses water • Reduce wax formation • Improves lubricity for prolonged pump & injector life • Reduces filter plugging • Prevents fuel line & filter icing • Improves fuel flow for quicker starting • Decreases emissions • Reduces smoke up to 50% • Improves performance & fuel economy 	<p>Solution:</p> <p>Problem solver – Bio Rid™ Diesel Fuel Protector</p> <ul style="list-style-type: none"> • Removes sediment • Keeps injectors clean • Absorbs & disperses moisture • Improves storage stability • Controls corrosion • Keeps fuel tank lines & filters clean
<p>ANTI-GEL</p> <p>C-23, C-24, C-270, C-272, C-DFA</p> <p>Anti-Gel Diesel Fuel Treatment</p> <p>1 gal treats 1,000 gallons; 32 oz treats 250 gallons; Super concentrated C-DFA treats 50 gallons; C-23 (8 oz) treats up to 10 gallons.</p> 	<p>POWERFUL CLEANER</p> <p>C-21, C-260 & C-261</p> <p>Diesel Fuel Injector Cleaner</p> <p>8 oz treats 10-15 gallons; 12 oz treats 10-25 gallons; 32 oz treats up to 150 gallons. Use every 15,000 miles.</p> 	<p>NO ALCOHOL</p> <p>C-285 Diesel Water Remover</p> <p>Trucks and large diesels use 12 oz. with every fill-up. Smaller trucks, vans & passenger cars use 12 oz. in every other tankful until problem is eliminated.</p> 	<p>FAST RESULTS</p> <p>POWERFUL CLEANER - DIESEL CLEAN EXHAUST™</p> <p>C-295 Diesel Clean Exhaust™</p> <p>For best results, add contents before filling tank with fuel. One quart treats up to 125 gallons. Use every 30,000 to 35,000 miles and at least 1,000 miles prior to emissions testing.</p> 	<p>ANTI-GEL</p> <p>C-280 Diesel Instant Thaw™</p> <p>When a problem exists, remove the filter housing. Dump instant Thaw into the filter. Replace the filter and drive. For best results, add contents prior to fill-up. One quart treats up to 150 gallons.</p> 	<p>PROTECTOR</p> <p>C-275 Bio Rid™ Diesel Fuel Protector</p> <p>Treats 50 gallons. For uniform dispersion, add entire bottle when tank is half filled. First-time usage use two bottles to clean system quickly. To keep clean, use one bottle every third or fourth tankful.</p> 



Cyclo Industries, LLC
 10190 Riverside Drive
 Palm Beach Gardens, FL 39410
 Toll Free (800) 843-7813
 (561) 775-9600 • Fax (561) 622-1055
 e-mail: cyclo@cyclo.com
 www.cyclo.com

©2004 Cyclo Industries, LLC



MADE WITH PRIDE IN THE U.S.A.

The Professional Choice For More Than 40 Years!

Form #0448